

ODS-AGM16CL (PC625)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage		12V
Capacity (20-hour rate)		18Ah
Capacity (10-hour rate)		17Ah
Cold Cranking Amps (CCA,	SAE J537)	220A
PHCA - 5-second pulse cur	rent	540A
HCA		400A
MCA		330A
Reserve capacity		26 mins
Short circuit current (using	IEC method)	1800A
Internal resistance at 20°C	C (using IEC method)	$7~\text{m}\Omega$

Dimensions & Weight

Length	170 mm
Width	99 mm
Height (to top of terminals)	178 mm
Height Container	175 mm
Weight	6 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.


Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%


Fitting, handling & storage


Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

Terminal Position




Terminal Type





ODS-AGM16CL RIGHT POSITIVE FRONT FEMALE CONNECTION



PDF Generated at https://eu.odysseybattery.com 13/09/2021 13:30:58 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-610-208-1991 / +1-800-538-3627 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780